



## Main

|                           |                      |
|---------------------------|----------------------|
| Range                     | TeSys<br>TeSys Deca  |
| Device short name         | GVAU                 |
| Product or Component Type | Undervoltage release |

## Complementary

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range compatibility             | TeSys GV2ME<br>TeSys GV2LE<br>TeSys GV2L<br>TeSys GV2P<br>TeSys GV3L<br>TeSys GV3P<br>TeSys Deca                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| [Uc] control circuit voltage    | 380...400 V AC 50 Hz<br>440 V AC 60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Control circuit voltage limits  | 0.85...1.1 Un                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| [Ui] rated insulation voltage   | 690 V AC IEC 60947-1<br>600 V AC UL 60947-4-1<br>600 V AC CSA C22.2 No 60947-4-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Threshold tripping voltage      | 0.7...0.35 Un                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Inrush power in VA              | 12 VA AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Inrush power in W               | 8 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Hold-in Power Consumption in VA | 3.5 VA AC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Hold-in power consumption in W  | 1.1 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Operating time                  | 10...15 ms IEC 60947-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| On-load factor                  | 100 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Connections - terminals         | Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )solid<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )solid<br>Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible without cable end<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> )flexible without cable end<br>Screw clamp terminals 1 0.00...0.00 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> )flexible with cable end<br>Screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (0.75...1.5 mm <sup>2</sup> )flexible with cable end |
| Tightening torque               | < 1.4 N.m screw clamp terminals                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Mechanical durability           | 10000 Cycles with GV3P and GV3L<br>30000 cycles with GV2ME and GV2P                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Quantity per Set                | Set of 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Height                          | 3.50 in (89 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Width                           | 0.71 in (18 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Depth                           | 2.60 in (66 mm)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Net Weight                      | 0.23 lb(US) (0.105 kg)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Color                           | Dark grey                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

## Ordering and shipping details

|                   |                                  |
|-------------------|----------------------------------|
| Category          | 22367-MANUAL STR PROTECTOR - GV2 |
| Discount Schedule | I11                              |
| GTIN              | 3389110346022                    |
| Returnability     | Yes                              |
| Country of origin | CZ                               |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Number of Units in Package 1 | 1                       |
| Package 1 Height             | 1.46 in (3.700 cm)      |
| Package 1 Width              | 3.35 in (8.500 cm)      |
| Package 1 Length             | 3.66 in (9.300 cm)      |
| Package 1 Weight             | 3.84 oz (109.000 g)     |
| Unit Type of Package 2       | S02                     |
| Number of Units in Package 2 | 42                      |
| Package 2 Height             | 5.91 in (15.000 cm)     |
| Package 2 Width              | 11.81 in (30.000 cm)    |
| Package 2 Length             | 15.75 in (40.000 cm)    |
| Package 2 Weight             | 10.65 lb(US) (4.830 kg) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                           |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                     |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                         |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                       |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                             |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                                       |
| Mercury free               | Yes                                                                                                                                                                                                                                                       |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                    |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                             |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                                                   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                              |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

---

GVAU...

