




MBR20H100CT - MBR20H200CT

20.0AMPS. Schottky Barrier Rectifiers

TO-220AB

Features

- ✧ Plastic material used carriers Underwriters Laboratory Classification 94V-0
- ✧ Metal silicon junction, majority carrier conduction
- ✧ Low power loss, high efficiency
- ✧ High current capability, low forward voltage drop
- ✧ High surge capability
- ✧ For use in power supply - output rectification, power management, instrumentation
- ✧ Guard-ring for overvoltage protection
- ✧ High temperature soldering guaranteed:
260°C/10 seconds 0.25", (6.35mm) from case
- ✧ Green compound with suffix "G" on packing code & prefix "G" on datecode



Mechanical Data

- ✧ Cases: JEDEC TO-220AB molded plastic body
- ✧ Terminals: Pure tin plated, lead free, solderable per MIL-STD-750, Method 2026
- ✧ Polarity: As marked
- ✧ Mounting position: Any
- ✧ Mounting torque: 5 in. - lbs, max
- ✧ Weight: 1.82 grams

Dimensions in inches and (millimeters)



Marking Diagram

MBR20HXXCT = Specific Device Code

G = Green Compound

Y = Year

WW = Work Week

Maximum Ratings and Electrical Characteristics

Rating at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	MBR 20H100CT	MBR 20H150CT	MBR 20H200CT	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	100	150	200	V
Maximum RMS Voltage	V _{RMS}	70	105	140	V
Maximum DC Blocking Voltage	V _{DC}	100	150	200	V
Maximum Average Forward Rectified Current	I _{F(AV)}	20			A
Peak Repetitive Surge Current (Rated V _R , Square Wave, 20KHz)	I _{FRM}	20			A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	150			A
Peak Repetitive Reverse Surge Current (Note 1)	I _{RRM}	1.0		0.5	A
Maximum Instantaneous Forward Voltage at (Note 2) IF=10A, T _A =25°C IF=10A, T _A =125°C IF=20A, T _A =25°C IF=20A, T _A =125°C	V _F	0.85 0.75 0.95 0.85	0.88 0.75 0.97 0.85		V
Maximum Instantaneius Reverse Current at Rated DC Blocking Voltage	I _R	5			uA
		2			mA
Voltage Rate of Change,(Rated V _R)	dV/dt	10,000			V/us
Maximum Typical Thermal Resistance	R _{θJC}	1.5			°C/W
Operating Junction Temperature Range	T _J	- 65 to + 175			°C
Storage Temperature Range	T _{STG}	- 65 to + 175			°C

Note 1: 2.0uS Pulse Width, f=1.0KHz

Note 2: Pulse Test : 300uS Pulse Width, 1% Duty Cycle

RATINGS AND CHARACTERISTIC CURVES (MBR20H100CT THRU MBR20H200CT)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG. 2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT PER LEG




FIG.3- TYPICAL INSTANTANEOUS FORWARD CHARACTERISRICS PER LEG




FIG. 4- TYPICAL REVERSE CHARACTERISTICS PER LEG




FIG. 5- TYPICAL JUNCTION CAPACITANCE PER LEG




FIG. 6- TYPICAL TRANSIENT THERMAL IMPEDANCE PER LEG

