# RT-770-1/2-0-SP - ACTIVE

#### **RAYCHEM**

TE Internal #: D56022-000

Black, 2:1, Single Wall Tubing, Shrinks To .25 in [6.4 mm],


Crosslinked Fluoroelastomer, .5 in [12.7 mm] Inner Diameter, Highly

Flame-Retardant, Piece

View on TE.com >



Heat Shrink Tubing > Single Wall RT 770: Heat Shrink Tubing, 2:1 Shrink Ratio



Primary Product Color: Black

Wall Type: Single Wall

Expanded Inside Diameter (Min): 12.7 mm [.5 in]
Recovered Inside Diameter (Max): 6.4 mm [.25 in]

Shrink Ratio: 2:1

All Single Wall RT 770: Heat Shrink Tubing, 2:1 Shrink Ratio (10)

### **Features**

### **Product Type Features**

Wall Type	Single Wall
Body Features	
Material Systems Code	770
Fluid Type	Aviation Fuel, Brake Fluid, Chemicals /Solvents, De-Icing Fluid, Diesel Fuel, Hydraulic Fluid, Lubricating Oil, Military Decontaminating Agents, Water
Primary Product Color	Black
Shrink Ratio	2:1
Primary Product Material	Crosslinked Fluoroelastomer
Flexibility	Flexible
Dimensions	
Recovered Wall Thickness (Nominal)	.08 mm[.003 in]
Expanded Inside Diameter (Min)	12.7 mm[.5 in]
Recovered Inside Diameter (Max)	6.4 mm[.25 in]
Tubing Size Range	6.4 – 12.7 mm[.25 – .5 in]
Usage Conditions	

150 °C

Shrink Temperature (Min)



Resistance Properties	Moisture
Tubing Flammability Type	Highly Flame-Retardant
Operating Temperature Range	-55 – 125 °C
Recovery Temperature	150 °C
Operation/Application	
Mechanical Resistance	Fluids
Product Availability	
Applicable Region	Worldwide
Packaging Features	
Packaging Method	Piece
Other	
Meets Low Outgassing Requirements	No
Product Source	US

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides




on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Customers Also Bought

















### **Documents**

Product Drawings RT-770-1/2-0-SP

English

Datasheets & Catalog Pages

1654025\_Sec3\_RT-770

English

raychem-tubing-product-selection-guide

English

**Product Specifications** 

**Product Specification** 

English