

### Kilovac | Kilovac LEV100

TE Internal #: 4-1618391-0

DC Contactors, Contact Arrangement 1 Form X, SPST-NO DM, 22 AWG Wire Size, .34 mm<sup>2</sup> Wire Size, 100A Contact Current Rating, Kilovac LEV100

View on TE.com >



Relays & Contactors > Contactors > Mil-Aero Contactors > DC Contactors



Contact Arrangement: 1 Form X, SPST-NO DM

Wire Size: .34 mm<sup>2</sup>

Contact Current Rating: 100 A

Coil Resistance: 26 Ω

## **Features**

#### **Configuration Features**

Configuration Features	
Auxiliary Switch Contact Arrangement	None
Contact Arrangement	1 Form X, SPST-NO DM
Number of Poles	1
Electrical Characteristics	
Contact Current Rating	100 A
Coil Resistance	26 Ω
Coil Voltage Rating	12 VDC
Contact Switching Voltage (Max)	900 VDC
Body Features	
Enclosure Type	Sealed
Termination Features	
Main Termination & Connection Type	M5 Female
Coil Termination & Connection Type	Connector
Mechanical Attachment	
Torque (Main)	30 – 40 in-lbs

Chassis

381 mm[15 in]

Product Mount Type

Coil Wire Length

**Dimensions** 



Wire Size	.34 mm <sup>2</sup>
Operation/Application	
Actuating System	DC
Packaging Features	

Individual

## **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (.35% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

## Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**

DC Contactors, Contact Arrangement 1 Form X, SPST-NO DM, 22 AWG Wire Size, . 34 mm² Wire Size, 100A Contact Current Rating, Kilovac LEV100





TE Part # 7-1618401-3 LEV200A4NAF01=Contactor, w/Coil





# Also in the Series | Kilovac LEV100



DC Contactors(11)



High Voltage Relays(2)

# Customers Also Bought









TE Part #1-1616973-1 BE429=ELECTRICAL LOAD **CONTROL UNIT** 

TE Part #1616973-9 B-241B=CONTACTOR - 3PST LATCHING 725A

TE Part #2221-8-7801 SLV CRIMP

TE Part #7-1616994-4 BEH-494H-1=CONTACTOR

## **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** ENG\_CVM\_CVM\_4-1618391-0\_D.2d\_dxf.zip

English

DC Contactors, Contact Arrangement 1 Form X, SPST-NO DM, 22 AWG Wire Size, . 34 mm² Wire Size, 100A Contact Current Rating, Kilovac LEV100



**Customer View Model** 

ENG\_CVM\_CVM\_4-1618391-0\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_4-1618391-0\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Kilovac LEV100 Series 900 Vdc Contactor

English